SECTION 1: Identification of the substance / preparation and of the company

1.1 Product identifier

SWAG 10 92 1829 gear oil
Article number 10 92 1829

1.2 Relevant identified uses of the substance or mixture and uses advised against

1.2.1 Relevant uses

Lubricant

1.2.2 Uses advised against

None known.

1.3 Details of the supplier of the safety data sheet

Company

SWAG Autoteile GmbH
Am Kiesberg 4-6
42117 Wuppertal / GERMANY
Phone +49 (0)202 26454-0
Fax +49 (0)202 26454-5000
Homepage www.swag.de
E-mail info@swag.de

Address enquiries to

Technical information	info@swag.de
Safety Data Sheet	info@swag.de

1.4 Emergency phone

Advisory body	+49 (0)89-19240 (24h) (english)
Company	+49 (0)202 26454-0

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

2.1.1 Classification according to Regulation (EC) No 1272/2008 [CLP]

not determined

2.1.2 Classification according to Regulation 67/548/EEC or 1999/45/EC

No classification.

2.2 Label elements

The product is required to be labelled in accordance with EC-Directives.

Labelling according to Regulation 67/548/EEC or 1999/45/EC

Hazard symbols	none
R-phrases	none
Special labelling	Contains: Ethanol, 2,2'-iminobis-, N-tallow alkyl derivs., Reaction products of bis(4-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14-alkyl (branched). May produce an allergic reaction.

2.3 Other hazards

Physico-chemical hazards	No particular hazards known.
Human health dangers	If swallowed or in the event of vomiting, risk of product entering the lungs. Frequent persistent contact with the skin can cause skin irritation.
Environmental hazards	Does not contain any PBT or vPvB substances.
Other hazards	none

SECTION 3: Composition / Information on ingredients

Product-type:

The product is a mixture.

Range [%]	Substance
0,1 - <1	Ethanol, 2,2'-iminobis-, N-tallow alkyl derivs.
	CAS: 61791-44-4, EINECS/ELINCS: 263-177-5
	GHS/CLP: Acute Tox. 4: H302 - Skin Corr. 1B: H314 - Skin Sens. 1: H317 - Aquatic Acute 1: H400
	EEC: C-N, R 22-34-43-50
0,1 - <1	Molybdenum, bis(ditridecylcarbamodithioato)di-oxodioxo-di-,sulfurized
	CAS: 71342-89-7, EINECS/ELINCS: 275-347-6
	GHS/CLP: Aquatic Chronic 2: H411
	EEC: Xi-N, R 38-51/53
0,1 - <1	Reaction products of bis(4-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14-alkyl (branched)
	EINECS/ELINCS: 931-384-6, ECB-Nr.: 01-2119493620-38-XXXX
	GHS/CLP: Acute Tox. 4: H302 - Eye Dam. 1: H318 - Skin Sens. 1: H317 - Aquatic Chronic 2: H411 - Flam. Liq. 3: H226
	EEC: Xn-N, R 22-41-43-51/53
0,1 - <1	alkoxylated alkylphenol
	EINECS/ELINCS: 618-541-1
	GHS/CLP: Eye Irrit. 2: H319 - Aquatic Chronic 2: H411
	EEC: Xi-N, R 36/38-51/53

Comment on component parts SVHC (Candidate List of Substances of Very High Concern for authorisation) ≥ 0,1%
CAS - alkoxylated alkylphenol
For full text of H-statements and R-phrases: see SECTION 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information Change soaked clothing.

Inhalation Ensure supply of fresh air.
In the event of symptoms seek for medical treatment.

Skin contact When in contact with the skin, clean with soap and water.
Consult a doctor if skin irritation persists.

Eye contact Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
If eye irritation persists: Get medical advice/attention.

Ingestion Do not induce vomiting.
Rinse out mouth and give plenty of water to drink.
Supply with medical care.

4.2 Most important symptoms and effects, both acute and delayed

Headache

4.3 Indication of any immediate medical attention and special treatment needed

Treat symptomatically.
If swallowed or in the event of vomiting, risk of product entering the lungs.
Forward this sheet to the doctor.

SECTION 5: Fire-fighting measures

5.1 Extinguishing media

Suitable extinguishing media Foam, dry powder, water spray jet, carbon dioxide.

Extinguishing media that must not be used Full water jet.

5.2 Special hazards arising from the substance or mixture

Not combusted hydrocarbons.
Unknown risk of formation of toxic pyrolysis products.
Carbon monoxide (CO)

5.3 Advice for firefighters

Do not inhale explosion and/or combustion gases.
Use self-contained breathing apparatus.

Cool containers at risk with water spray jet.
Fire residues and contaminated firefighting water must be disposed of in accordance within the local regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

High risk of slipping due to leakage/spillage of product.
Forms slippery surfaces with water.

6.2 Environmental precautions

Prevent spread over a wide area (e.g. by containment or oil barriers).
Do not discharge into the drains/surface waters/groundwater.

6.3 Methods and material for containment and cleaning up

Take up with absorbent material (e.g. general-purpose binder).
Dispose of absorbed material in accordance within the regulations.

6.4 Reference to other sections

See SECTION 8+13

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Avoid formation of aerosols.

Do not eat, drink, smoke or take drugs at work.
Use barrier skin cream.
Wash hands before breaks and after work.
Cloths contaminated with product should not be kept in trouser pockets.
Contaminated work clothing should not be allowed out of the workplace.
Take off contaminated clothing and wash before reuse.

7.2 Conditions for safe storage, including any incompatibilities

Keep only in original container.
Prevent penetration into the ground.

Do not store together with food and animal food/diet.

Keep container tightly closed.
Keep container in a well-ventilated place.

7.3 Specific end use(s)

See product use, SECTION 1.2

SECTION 8: Exposure controls / personal protection

Ingredients with occupational exposure limits to be monitored (GB)

8.1 Control parameters

not applicable

DNEL

Range [%]	Substance
0,1 - <1	Reaction products of bis(4-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14-alkyl (branched)
	Industrial, inhalative, Long-term - systemic effects: 8,56 mg/m³/8h (ECHA CHEM).
	Industrial, dermal, Long-term - systemic effects: 12,5 mg/kg/8h (ECHA CHEM).

PNEC

Range [%]	Substance
0,1 - <1	Reaction products of bis(4-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14-alkyl (branched)
	sewage treatment plants (STP), 24.33 mg/l (ECHA CHEM).
	soil, 2,54 mg/kg soil dw (ECHA CHEM).
	sediment (marine water), 0,313 mg/kg (ECHA CHEM).
	sediment (fresh water), 3,13 mg/kg (ECHA CHEM).
	marine water, 0,00012 mg/l (ECHA CHEM).
	fresh water, 0,0012 mg/l (ECHA CHEM).

8.2 Exposure controls

Additional advice on system design
Ensure adequate ventilation on workstation.

Eye protection
If there is a risk of splashing:
Safety glasses.

Hand protection
The details concerned are recommendations. Please contact the glove supplier for further information.
Nitrile rubber, >480 min (EN 374).
Neoprene, >480 min (EN 374).

Skin protection
Light protective clothing.

Other
Personal protective equipment should be selected specifically for the working place, depending on concentration and quantity of the hazardous substances handled. The resistance of these equipments to chemicals should be ascertained with the respective supplier.
Avoid contact with eyes and skin.

Respiratory protection
Breathing apparatus in the event of high concentrations.
Short term: filter apparatus, combination filter A-P1.

Thermal hazards
No information available.

Delimitation and monitoring of the environmental exposition
See SECTION 6+7.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Form	liquid
Color	light yellow
Odor	characteristic
Odour threshold	not determined
pH-value	not applicable
pH-value [1%]	not applicable
Boiling point [°C]	not determined
Flash point [°C]	221 (ISO 2592)
Flammability [°C]	not determined
Lower explosion limit	not applicable
Upper explosion limit	not applicable
Oxidizing properties	no
Vapour pressure/gas pressure [kPa]	not determined
Density [g/ml]	0,877 (DIN 51757) (15 °C / 59,0 °F)
Bulk density [kg/m³]	not applicable
Solubility in water	immiscible
Partition coefficient [n-octanol/water]	not determined
Viscosity	41 mm²/s (40°C); (DIN 51562)
Relative vapour density determined in air	not determined
Evaporation speed	not determined
Melting point [°C]	not determined
Autoignition temperature [°C]	not applicable
Decomposition temperature [°C]	not determined

9.2 Other information

none

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reactions known if used as directed.

10.2 Chemical stability

Stable under normal ambient conditions (ambient temperature).

10.3 Possibility of hazardous reactions

Reactions with strong oxidizing agents.

10.4 Conditions to avoid

See SECTION 7.2.

10.5 Incompatible materials

No information available.

10.6 Hazardous decomposition products

No hazardous decomposition products known.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Range [%]	Substance
0,1 - <1	Reaction products of bis(4-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14-alkyl (branched)
	LD50, oral, Rat: 2000 mg/kg bw OECD 401 (ECHA CHEM).

Serious eye damage/irritation	not determined
Skin corrosion/irritation	not determined
Respiratory or skin sensitisation	not determined
Specific target organ toxicity — single exposure	not determined
Specific target organ toxicity — repeated exposure	not determined
Mutagenicity	not determined
Reproduction toxicity	not determined
Carcinogenicity	not determined
General remarks	

No classification on the basis of the calculation procedure of the preparation directive.
Toxicological data of complete product are not available.

SECTION 12: Ecological information

12.1 Toxicity

Range [%]	Substance
0,1 - <1	Reaction products of bis(4-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14-alkyl (branched)
	EL50, (48h), Daphnia magna: ~ 91,4 mg/l OECD 202 (ECHA CHEM).
	EL50, (96h), Selenastrum capricornutum: > 15 mg/l OECD 201 (ECHA CHEM).
	LL50, (96h), Oncorhynchus mykiss: ~ 24 mg/l OECD 203 (ECHA CHEM).

12.2 Persistence and degradability

Behaviour in environment compartments	not determined
Behaviour in sewage plant	not determined
Biological degradability	The product is slightly soluble in water. It can be largely eliminated from the water by abiotic processes, e.g. mechanical separation.

12.3 Bioaccumulative potential

No information available.

12.4 Mobility in soil

No information available.

12.5 Results of PBT and vPvB assessment

Based on all available information not to be classified as PBT or vPvB respectively.

12.6 Other adverse effects

No classification on the basis of the calculation procedure of the preparation directive.
Ecological data of complete product are not available.
Do not discharge product unmonitored into the environment or into the drainage.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Waste material must be disposed of in accordance with the Directive on waste 2008/98/EC as well as other national and local regulations. It is not possible to determine a waste code for this product in accordance with the European Waste Catalogue (EWC) since it is only possible to classify it according to how it is used by the customer. The waste code is to be determined within the EU in liaison with the waste-disposal operator.

Product

Disposal in an incineration plant in accordance with the regulations of the local authorities.
In according to RoHS!
Coordinate disposal with the authorities if necessary.

Waste no. (recommended) 130205* mineral-based non-chlorinated engine, gear and lubricating oils

Contaminated packaging

Uncontaminated packaging may be taken for recycling.
Packaging that cannot be cleaned should be disposed of as for product.

Waste no. (recommended) 150110*

SECTION 14: Transport information

14.1 UN number

See SECTION 14.2 in accordance with UN shipping name

14.2 UN proper shipping name

Transport by land according to ADR/RID NO DANGEROUS GOODS

Inland navigation (ADN) NO DANGEROUS GOODS

Marine transport in accordance with IMDG NOT CLASSIFIED AS "DANGEROUS GOODS"

Air transport in accordance with IATA NOT CLASSIFIED AS "DANGEROUS GOODS"

14.3 Transport hazard class(es)

See SECTION 14.2 in accordance with UN shipping name

14.4 Packing group

See SECTION 14.2 in accordance with UN shipping name

14.5 Environmental hazards

See SECTION 14.2 in accordance with UN shipping name

14.6 Special precautions for user

Relevant information under SECTION 6 to 8.

14.7 Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

not applicable

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EEC-REGULATIONS	1967/548 (1999/45); 1991/689 (2001/118); 1999/13; 2004/42; 648/2004; 1907/2006 (Reach); 1272/2008; 75/324/EEC (2008/47/EC); 453/2010/EC
TRANSPORT-REGULATIONS	DOT-Classification, ADR (2013); IMDG-Code (2013, 36. Amdt.); IATA-DGR (2013).
NATIONAL REGULATIONS (GB):	EH40/2005 Workplace exposure limits (Second edition, published December 2011). CHIP 3/ CHIP 4
- Observe employment restrictions for people	no
- VOC (1999/13/CE)	0 %

15.2 Chemical safety assessment

not applicable

SECTION 16: Other information

16.1 R-phrases (SECTION 3)

R 36/38: Irritating to eyes and skin.
R 51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R 22: Harmful if swallowed.
R 41: Risk of serious damage to eyes.
R 43: May cause sensitisation by skin contact.
R 38: Irritating to skin.
R 34: Causes burns.
R 50: Very toxic to aquatic organisms.

16.2 Hazard statements (SECTION 3)

H400 Very toxic to aquatic life.
H314 Causes severe skin burns and eye damage.
H226 Flammable liquid and vapour.
H317 May cause an allergic skin reaction.
H318 Causes serious eye damage.
H302 Harmful if swallowed.
H411 Toxic to aquatic life with long lasting effects.
H319 Causes serious eye irritation.

16.3 Abbreviations and acronyms:

ADR = Accord européen relatif au transport international des marchandises Dangereuses par Route
RID = Règlement concernant le transport international ferroviaire de marchandises dangereuses
ADN = Accord européen relatif au transport international des marchandises dangereuses par voie de navigation intérieure
CAS = Chemical Abstracts Service
CLP = Classification, Labelling and Packaging
DMEL = Derived Minimum Effect Level
DNEL = Derived No Effect Level
EC50 = Median effective concentration
ECB = European Chemicals Bureau
EEC = European Economic Community
EINECS = European Inventory of Existing Commercial Chemical Substances
ELINCS = European List of Notified Chemical Substances
GHS = Globally Harmonized System of Classification and Labelling of Chemicals
IATA = International Air Transport Association
IBC-Code = International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk
IC50 = Inhibition concentration, 50%
IMDG = International Maritime Code for Dangerous Goods
IUCLID = International Uniform ChemicaL Information Database
LC50 = Lethal concentration, 50%
LD50 = Median lethal dose
MARPOL = International Convention for the Prevention of Marine Pollution from Ships
PBT = Persistent, Bioaccumulative and Toxic substance
PNEC = Predicted No-Effect Concentration
REACH = Registration, Evaluation, Authorisation and Restriction of Chemicals
TLV®/TWA = Threshold limit value – time-weighted average
TLV®STEL = Threshold limit value – short-time exposure limit
VOC = Volatile Organic Compounds
vPvB = very Persistent and very Bioaccumulative

16.4 Other information

Modified position

SECTION 4 been added: Forward this sheet to the doctor.

SECTION 4 been added: If eye irritation persists: Get medical advice/attention.

SECTION 4 been added: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

SECTION 7 been added: Take off contaminated clothing and wash before reuse.

SECTION 7 been added: Contaminated work clothing should not be allowed out of the workplace.

SECTION 8 been added: If there is a risk of splashing: