

SWAG Autoteile GmbH 42117 Wuppertal

Date printed 03.04.2014, Revision 03.04.2014

Version 04. Supersedes version: 03

Page 1 / 9

SECTION 1: Identification of the substance / preparation and of the company

1.1 Product identifier

SWAG 99 90 2374 antifreeze

Article number 99 98 8541, 99 98 9428, 99 97 5011, 99 90 2374, 99 90

2374-1

1.2 Relevant identified uses of the substance or mixture and uses advised against

1.2.1 Relevant uses

Anti-freezing agents

1.2.2 Uses advised against

None known.

1.3 Details of the supplier of the safety data sheet

Company SWAG Autoteile GmbH

Am Kiesberg 4-6

42117 Wuppertal / GERMANY Phone +49 (0)202 26454-0 Fax +49 (0)202 26454-5000 Homepage www.swag.de E-mail info@swag.de

Address enquiries to

Technical information info@swag.de Safety Data Sheet info@swag.de

1.4 Emergency phone

Advisory body +49 (0)89-19240 (24h) (english)

Company +49 (0)202 26454-0

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

2.1.1 Classification according to Regulation (EC) No 1272/2008 [CLP]

see SECTION 16

2.1.2 Classification according to Regulation 67/548/EEC or 1999/45/EC

Xn, Harmful - R 22: Harmful if swallowed.

2.2 Label elements

Labelling according to Regulation 67/548/EEC or 1999/45/EC

The product is classified and required to be labelled in accordance with EC-Directives

Hazard symbols

Harmful

Contains: Ethylene glycol

R-phrases R 22: Harmful if swallowed.

S-phrases S 2: Keep out of the reach of children.

S 46: If swallowed, seek medical advice immediately and show this container or label.

2.3 Other hazards

Physico-chemical hazards No particular hazards known.

Human health dangers If swallowed or in the event of vomiting, risk of product entering the lungs.

Frequent persistent contact with the skin can cause skin irritation.

Other hazards Further hazards were not determined with the current level of knowledge.



SWAG Autoteile GmbH 42117 Wuppertal

Date printed 03.04.2014, Revision 03.04.2014

Version 04. Supersedes version: 03

Page 2 / 9

SECTION 3: Composition / Information on ingredients

Product-type:

The product is a mixture.

Range [%]	Substance
90 - 95	Ethylene glycol
	CAS: 107-21-1, EINECS/ELINCS: 203-473-3, EU-INDEX: 603-027-00-1, ECB-Nr.: 01-2119456816-28-XXXX
	GHS/CLP: Acute Tox. 4: H302 - STOT RE 2: H373
	EEC: Xn, R 22
1 - <5	Sodium 2-ethylhexanoate
	CAS: 19766-89-3, EINECS/ELINCS: 243-283-8
	GHS/CLP: Repr. 2: H361d
	EEC: Xn, R 63
< 1	disodium tetraborate
	CAS: 1330-43-4, EINECS/ELINCS: 215-540-4, EU-INDEX: 005-011-00-4
	GHS/CLP: Repr. 1B: H360F
	EEC: T, R 60-61

Comment on component parts SVHC (Candidate List of Substances of Very High Concern for authorisation) ≥ 0,1%

CAS 1330-43-4 - disodium tetraborate

For full text of H-statements and R-phrases: see SECTION 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information Change soaked clothing.

Inhalation Ensure supply of fresh air.

In the event of symptoms seek for medical treatment.

Skin contact In case of contact with skin wash off immediately with soap and water.

Consult a doctor if skin irritation persists.

Eye contact Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy

to do. Continue rinsing.

If eye irritation persists: Get medical advice/attention.

Ingestion Consult a doctor immediately.

Rinse out mouth and give plenty of water to drink.

Do not induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed

Diarrhoea Spasms Tiredness

4.3 Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

Forward this sheet to the doctor.

SECTION 5: Fire-fighting measures

5.1 Extinguishing media

Suitable extinguishing media Carbon dioxide.

Water spray jet. Dry powder. Foam.

Extinguishing media that must not

be used

Full water jet.

5.2 Special hazards arising from the substance or mixture

Unknown risk of formation of toxic pyrolysis products.

Carbon monoxide (CO)

SWAG® GERMANY

SWAG Autoteile GmbH 42117 Wuppertal

Date printed 03.04.2014, Revision 03.04.2014

Version 04. Supersedes version: 03

Page 3 / 9

5.3 Advice for firefighters

Use self-contained breathing apparatus.

Fire residues and contaminated firefighting water must be disposed of in accordance within

the local regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

High risk of slipping due to leakage/spillage of product.

Forms slippery surfaces with water.

6.2 Environmental precautions

Prevent spread over a wide area (e.g. by containment or oil barriers).

Do not discharge into the drains/surface waters/groundwater.

6.3 Methods and material for containment and cleaning up

Pick up with absorbent material (e.g. sand, sawdust, universal absorbent, diatomaceous

earth).

Dispose of absorbed material in accordance within the regulations.

6.4 Reference to other sections

See SECTION 8+13

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Use only in well-ventilated areas.

The product is combustible.

Contaminated work clothing should not be allowed out of the workplace.

Do not eat, drink or smoke when using this product.

Use barrier skin cream.

Wash hands before breaks and after work.

Take off contaminated clothing and wash before reuse.

7.2 Conditions for safe storage, including any incompatibilities

Keep only in original container.

Prevent penetration into the ground.

Do not store together with oxidizing agents.

Do not store together with food and animal food/diet.

Keep container in a well-ventilated place.

Keep container tightly closed.

7.3 Specific end use(s)

See product use, SECTION 1.2



SWAG Autoteile GmbH 42117 Wuppertal

Date printed 03.04.2014, Revision 03.04.2014

Version 04. Supersedes version: 03

Page 4 / 9

SECTION 8: Exposure controls / personal protection

8.1 Control parameters

Ingredients with occupational exposure limits to be monitored (GB)

-	
Range [%]	Substance
90 - 95	Ethylene glycol
	CAS: 107-21-1, EINECS/ELINCS: 203-473-3, EU-INDEX: 603-027-00-1, ECB-Nr.: 01-2119456816-28-XXXX
	Long-term exposure: 20 ppm, 52 mg/m³, Vapour, particulate: 10 mg/m³
	Short-term exposure (15-minute): 40 ppm, 104 mg/m³
0,1 - <0,5	disodium tetraborate
	CAS: 1330-43-4, EINECS/ELINCS: 215-540-4, EU-INDEX: 005-011-00-4
	Long-term exposure: 1 mg/m³

Ingredients with occupational exposure limits to be monitored (EU)

-	
Range [%]	Substance / EC LIMIT VALUES
90 - 95	Ethylene glycol
	CAS: 107-21-1, EINECS/ELINCS: 203-473-3, EU-INDEX: 603-027-00-1, ECB-Nr.: 01-2119456816-28-XXXX
	Eight hours: 20 ppm, 52 mg/m³, H
	Short-term (15-minute): 40 ppm, 104 mg/m³

DNEL

Range [%]	Substance
90 - 95	Ethylene glycol, CAS: 107-21-1
	Industrial, dermal, Long-term - systemic effects: 106 mg/m³.
	Industrial, inhalative, Long-term - local effects: 35 mg/m³.
	general population, dermal, Long-term - systemic effects: 53 mg/m³.
	general population, inhalative, Long-term - local effects: 7 mg/m³.

PNEC

Range [%]	Substance
90 - 95	Ethylene glycol, CAS: 107-21-1
	soil, 1,53 mg/kg.
	sediment (freshwater), 20,9 mg/kg.
	sewage treatment plants (STP), 199,5 mg/l.
	seawater, 1 mg/l.
	freshwater, 10 mg/l.

8.2 Exposure controls

Additional advice on system design

Ensure adequate ventilation on workstation.

Eye protection Safety glasses.

Hand protection The details concerned are recommendations. Please contact the glove supplier for further

information.

Nitrile rubber, >480 min (EN 374).

Skin protection Light protective clothing.

Other Personal protective equipment should be selected specifically for the working place,

depending on concentration and quantity of the hazardous substances handled. The resistance of these equipments to chemicals should be ascertained with the respective

supplier.

Avoid contact with eyes and skin.

Do not inhale vapours.

No information available.

Respiratory protection Breathing apparatus in the event of high concentrations.

Short term: filter apparatus, combination filter A-P2.

Thermal hazards

Delimitation and monitoring of the environmental exposition

See SECTION 6+7.



SWAG Autoteile GmbH 42117 Wuppertal

Date printed 03.04.2014, Revision 03.04.2014

Version 04. Supersedes version: 03

Page 5 / 9

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Form liquid
Color yellow/green
Odor mild

Odour threshold not determined pH-value 7,5 - 9 (50%) pH-value [1%] not determined Boiling point [°C] not determined > 100 (DIN 51758) Flash point [°C] Flammability [°C] > 400 (DIN 51794) Lower explosion limit not determined Upper explosion limit not determined

Oxidizing properties no

Vapour pressure/gas pressure [kPa] < 0,01 (20°C)

Density [g/ml] ~1,12 (DIN 51757) (20 °C / 68,0 °F)

 Bulk density [kg/m³]
 not applicable

 Solubility in water
 miscible

 Partition coefficient [n-octanol/water]
 not determined

 Viscosity
 not applicable

 Relative vapour density determined
 not determined

in al

Evaporation speed not determined

Melting point [°C] not determined

Autoignition temperature [°C] not applicable

Decomposition temperature [°C] not determined

9.2 Other information

none

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reactions known if used as directed.

10.2 Chemical stability

Stable under normal ambient conditions (ambient temperature).

10.3 Possibility of hazardous reactions

Reactions with acids, alkalies and oxidizing agents.

10.4 Conditions to avoid

See SECTION 7.2.

10.5 Incompatible materials

not determined

10.6 Hazardous decomposition products

No hazardous decomposition products known.



SWAG Autoteile GmbH 42117 Wuppertal

Date printed 03.04.2014, Revision 03.04.2014

Version 04. Supersedes version: 03

Page 6 / 9

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Range [%]	Substance
< 1	disodium tetraborate, CAS: 1330-43-4
	LD50, dermal, Rabbit: > 2000 mg/kg.
	LD50, oral, Rat: 2400 - 2600 mg/kg.
90 - 95	Ethylene glycol, CAS: 107-21-1
	LD50, dermal, mouse: > 3500 mg/kg.
	LD50, oral, Rat: 7712 mg/kg.
	LC50, inhalative, Rat: > 2,5 mg/l 6h.
	LDLo, oral, Human: ca. 1600 mg/kg.

Serious eye damage/irritation not determined
Skin corrosion/irritation not determined
Respiratory or skin sensitisation not determined
Specific target organ toxicity — not determined
single exposure

Specific target organ toxicity —

repeated exposure

not determined

 Mutagenicity
 not determined

 Reproduction toxicity
 not determined

 Carcinogenicity
 not determined

General remarks

The product was classified on the basis of the calculation procedure of the preparation directive.

Toxicological data of complete product are not available.

The toxicity data listed pertaining to the ingredients are intended for those working in the medicinal professions, experts for occupational health and safety and toxicologists. The toxicity data pertaining to the ingredients were supplied by the manufacturers of raw materials.

SECTION 12: Ecological information

12.1 Toxicity

-		
	Range [%]	Substance
	< 1	disodium tetraborate, CAS: 1330-43-4
		LC50, (96h), fish: 74 mg/l.
	90 - 95	Ethylene glycol, CAS: 107-21-1
		LC50, (96h), Pimephales promelas: 72860 mg/l.
		EC50, (96h), Selenastrum capricornutum: 6500 - 13000 mg/l.
		EC50, (48h), Daphnia magna: > 100 mg/l OECD 202.

12.2 Persistence and degradability

Behaviour in environment

not determined

compartments

Behaviour in sewage plant not determined Biological degradability not determined

12.3 Bioaccumulative potential

No information available.

12.4 Mobility in soil

No information available.



SWAG Autoteile GmbH 42117 Wuppertal

Date printed 03.04.2014, Revision 03.04.2014

Version 04. Supersedes version: 03

Page 7 / 9

12.5 Results of PBT and vPvB assessment

Based on all available information not to be classified as PBT or vPvB respectively.

12.6 Other adverse effects

No classification on the basis of the calculation procedure of the preparation directive. The toxicity data pertaining to the ingredients were supplied by the manufacturers of raw materials.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Waste material must be disposed of in accordance with the Directive on waste 2008/98/EC as well as other national and local regulations. It is not possible to determine a waste code for this product in accordance with the European Waste Catalogue (EWC) since it is only possible to classify it according to how it is used by the customer. The waste code is to be determined within the EU in liaison with the waste-disposal operator.

Product

Disposal in an incineration plant in accordance with the regulations of the local authorities.

Dispose of as hazardous waste.

Waste no. (recommended)

160114*

Contaminated packaging

Packaging that cannot be cleaned should be disposed of as for product.

Uncontaminated packaging may be taken for recycling.

Waste no. (recommended) 150102

150104 150110*

SECTION 14: Transport information

14.1 UN number

ADR/RID

See SECTION 14.2 in accordance with UN shipping name

14.2 UN proper shipping name

Transport by land according to

NO DANGEROUS GOODS

Inland navigation (ADN)

NO DANGEROUS GOODS

Marine transport in accordance with NOT CLASSIFIED AS "DANGEROUS GOODS"

IMDG

Air transport in accordance with IATA NOT CLASSIFIED AS "DANGEROUS GOODS"

14.3 Transport hazard class(es)

See SECTION 14.2 in accordance with UN shipping name

14.4 Packing group

See SECTION 14.2 in accordance with UN shipping name

14.5 Environmental hazards

See SECTION 14.2 in accordance with UN shipping name

14.6 Special precautions for user

Relevant information under SECTION 6 to 8.



SWAG Autoteile GmbH 42117 Wuppertal

Date printed 03.04.2014, Revision 03.04.2014

Version 04. Supersedes version: 03

Page 8 / 9

14.7 Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

not applicable

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EEC-REGULATIONS 1967/548 (1999/45); 1991/689 (2001/118); 1999/13; 2004/42; 648/2004; 1907/2006 (Reach);

1272/2008; 75/324/EEC (2008/47/EC); 453/2010/EC

TRANSPORT-REGULATIONS DOT-Classification, ADR (2013); IMDG-Code (2013, 36. Amdt.); IATA-DGR (2013).

NATIONAL REGULATIONS (GB): EH40/2005 Workplace exposure limits (Second edition, published December 2011).

CHIP 3/ CHIP 4

- Observe employment restrictions

for people

yes

- VOC (1999/13/CE) 0%

15.2 Chemical safety assessment

not applicable

SECTION 16: Other information

16.1 Classification according to Regulation (EC) No 1272/2008 [CLP]

Hazard pictograms

 $\langle ! \rangle$

Signal word WARNING

Acute Tox. 4: H302 Harmful if swallowed.

Classification procedure Classification according to conversion table Annex VII 1272/2008/EC

16.2 R-phrases (SECTION 3)

R 22: Harmful if swallowed.

R 63: Possible risk of harm to the unborn child.

R 60: May impair fertility.

R 61: May cause harm to the unborn child.

16.3 Hazard statements (SECTION 3)

H360D May damage the unborn child.

H360F May damage fertility.

H361d Suspected of damaging the unborn child.

H373 May cause damage to organs through prolonged or repeated exposure.

H302 Harmful if swallowed.

SWAG Autoteile GmbH 42117 Wuppertal

Date printed 03.04.2014, Revision 03.04.2014

Version 04. Supersedes version: 03

Page 9 / 9

16.4 Abbreviations and acronyms:

ADR = Accord européen relatif au transport international des marchandises Dangereuses par Route

RID = Règlement concernant le transport international ferroviaire de marchandises dangereuses

ADN = Accord européen relatif au transport international des marchandises dangereuses par voie de navigation intérieure

CAS = Chemical Abstracts Service

CLP = Classification, Labelling and Packaging

DMEL = Derived Minimum Effect Level DNEL = Derived No Effect Level EC50 = Median effective concentration

ECB = European Chemicals Bureau EEC = European Economic Community

EINECS = European Inventory of Existing Commercial Chemical Substances

ELINCS = European List of Notified Chemical Substances

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IATA = International Air Transport Association

IBC-Code = International Code for the Construction and Equipment of Ships carrying

Dangerous Chemicals in Bulk

IC50 = Inhibition concentration, 50%

IMDG = International Maritime Code for Dangerous Goods IUCLID = International Uniform ChemicaL Information Database

LC50 = Lethal concentration, 50%

LD50 = Median lethal dose

MARPOL = International Convention for the Prevention of Marine Pollution from Ships

PBT = Persistent, Bioaccumulative and Toxic substance

PNEC = Predicted No-Effect Concentration

REACH = Registration, Evaluation, Authorisation and Restriction of Chemicals

TLV®/TWA = Threshold limit value - time-weighted average TLV®STEL = Threshold limit value - short-time exposure limit VOC = Volatile Organic Compounds

vPvB = very Persistent and very Bioaccumulative

16.5 Other information

Modified position

SECTION 2 been added: The product is classified and required to be labelled in accordance with EC-Directives

SECTION 4 been added: If eye irritation persists: Get medical advice/attention.

SECTION 4 been added: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

SECTION 4 been added: Forward this sheet to the doctor.